

Version: 3.2 Revision Date: 05/07/2024

This is a kit that contains the following components: EUCOTHANE CLEAR PART A EUCOTHANE CLEAR PART B



Version: 3.2 Revision Date: 05/07/2024

SAFETY DATA SHEET

1. Identification

Product identifier: EUCOTHANE CLEAR PART A Product Code: CUSK G034 000

Recommended use and restriction on use

Recommended use: Coatings Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

EUCLID CHEMICAL COMPANY 19218 REDWOOD ROAD CLEVELAND OH 44110 US

Contact person: Telephone: Emergency telephone number:

EH&S Department 216-531-9222 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Physical	Hazards
----------	---------

	-lammable liquids		Category 3
He	Ith Hazards		
	Acute toxicity (Inhalation - vape	or)	Category 4
	Acute toxicity (Inhalation - dust nist)	and	Category 4
	Skin Corrosion/Irritation		Category 2
	Serious Eye Damage/Eye Irrita	ation	Category 2A
	Carcinogenicity		Category 2
	Foxic to reproduction		Category 1B
	Specific Target Organ Toxicity Repeated Exposure	-	Category 2 ^{1.}
	Specific Target Organ Toxicity	-	•••

Target Organs

1. hearing

Unknown toxicity - Health

Acute toxicity, oral	4 %
Acute toxicity, dermal	9.5 %
Acute toxicity, inhalation, vapor	66 %
Acute toxicity, inhalation, dust	66 %
or mist	

Environmental Hazards



Acute hazards to the aquatic environment	Category 3
Chronic hazards to the aquatic environment	Category 3
Unknown toxicity - Environment	
Acute hazards to the aquatic environment	59.5 %
Chronic hazards to the aquatic	59.5 %

Label Elements

Hazard Symbol:

environment



Signal Word:	Danger
Hazard Statement:	Flammable liquid and vapor. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. Suspected of causing cancer. May damage fertility. May damage the unborn child. May cause damage to organs through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects.
Precautionary Statements	
Prevention:	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Do not breathe dust/fume/gas/mist/vapors/spray. Wash face, hands and any exposed skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/ protective clothing/ eye protection/ face protection. Use personal protective equipment as required.
Response:	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. If skin irritation occurs: Get medical advice/attention. Specific treatment (see supplemental first aid instructions on this label). IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue 3/37



	rinsing. If eye irritation persists: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.
Storage:	Store in a well-ventilated place. Keep cool. Store locked up.
Disposal:	Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations.
Hazard(s) not otherwise classified (HNOC):	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Methyl n-amyl ketone	110-43-0	10 - <25%
Xylene	1330-20-7	10 - <20%
P-chlorobenzotrifluoride	98-56-6	5 - <10%
Ethylbenzene	100-41-4	1 - <2.5%
Dibutyl tin dilaurate	77-58-7	0.3 - <1%
Diisobutyl ketone	108-83-8	0.1 - <1%

All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Description of necessary first-aid measures		
Inhalation:	Move to fresh air.	
Skin Contact:	Take off immediately all contaminated clothing. Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. Get medical attention.	
Eye contact:	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.	
Ingestion:	Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.	
Personal Protection for First- aid Responders:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.	

Most important symptoms/effects, acute and delayed

Symptoms:	Respiratory tract irritation. may cause redness, itching, irri	Prolonged or repeated contact with skin tation and eczema/chapping.
Hazards:	No data available.	

Indication of immediate medical attention and special treatment needed



Treatment:	Symptoms may be delayed.
5. Fire-fighting measures	
General Fire Hazards:	Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move containers from fire area if you can do so without risk.
Suitable (and unsuitable) exting	uishing media
Suitable extinguishing media:	Use fire-extinguishing media appropriate for surrounding materials.
Unsuitable extinguishing media:	Avoid water in straight hose stream; will scatter and spread fire.
Specific hazards arising from the chemical:	Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of vapors or gases to explosive concentrations.
Special protective equipment a	nd precautions for fire-fighters
Special fire-fighting procedures:	No data available.
Special protective equipment for fire-fighters:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
6. Accidental release measure	28

Personal precautions, protective equipment and emergency procedures:	Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.
Accidental release measures:	In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.
Methods and material for containment and cleaning up:	Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.
Environmental Precautions:	Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.
7. Handling and storage	

Handling



Technical measures (e.g. Local and general ventilation):	Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.
Safe handling advice:	Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.Wash hands thoroughly after handling. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with eyes. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Avoid contact with skin.
Contact avoidance measures:	No data available.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Avoid contact with eyes. When
	using do not smoke. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Wash contaminated clothing before reuse. Avoid contact with skin.
Storage	using do not smoke. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Wash
Storage Safe storage conditions:	using do not smoke. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Wash

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Туре	Exposure Lim	it Values	Source
Methyl n-amyl ketone	TWA	50 ppm		US. ACGIH Threshold Limit Values, as amended (2011)
	PEL	100 ppm	465 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Ethylbenzene	TWA	20 ppm		US. ACGIH Threshold Limit Values, as amended (2011)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Chemical Identity	Туре	Exposure Lim	it Values	Source
Methyl n-amyl ketone	TWA	50 ppm		US. ACGIH Threshold Limit Values, as amended (2011)
	PEL	100 ppm	465 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Xylene	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	TWA	20 ppm		US. ACGIH Threshold Limit Values, as amended (01 2022)
Ethylbenzene	TWA	20 ppm		US. ACGIH Threshold Limit Values, as amended (2011)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air



				Contaminants (29 CFR 1910.1000), as amended (02 2006)
Diisobutyl ketone	PEL	50 ppm 290 n	ng/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	TWA	25 ppm		US. ACGIH Threshold Limit Values, as amended (2008)
Dibutyl tin dilaurate - as Sn	STEL	0.2 n	ng/m3	US. ACGIH Threshold Limit Values, as amended (2011)
	TWA	0.1 n	ng/m3	US. ACGIH Threshold Limit Values, as amended (2011)
	PEL	0.1 n	ng/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)

Chemical name	Туре	Exposure Lim	it Values	Source
Methyl n-amyl ketone	TWA	50 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)
Methyl n-amyl ketone	TWA	25 ppm	115 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Methyl n-amyl ketone	TWA	50 ppm	233 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
1-Methoxy-2-propanol acetate	TWA	50 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)
	STEL	75 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)
1-Methoxy-2-propanol acetate	TWA	50 ppm	270 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (12 2007)
Ethyl 3-ethoxypropionate	TWA	50 ppm	300 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (12 2007)
Ethylbenzene	TWA	20 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (09 2011)
Ethylbenzene	TWA	20 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Ethylbenzene	TWA	20 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)



Chemical name	Туре	Exposure Lim	it Values	Source
Methyl n-amyl ketone	TWA	50 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)
Methyl n-amyl ketone	TWA	25 ppm	115 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Methyl n-amyl ketone	TWA	50 ppm	233 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Xylene	STEL	150 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)
	TWA	100 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)
Xylene	STEL	150 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	TWA	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Xylene	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
	STEL	150 ppm	651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Ethylbenzene	TWA	20 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (09 2011)
Ethylbenzene	TWA	20 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Ethylbenzene	TWA	20 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)
Diisobutyl ketone	TWA	25 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)
Diisobutyl ketone	TWA	25 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Diisobutyl ketone	TWA	25 ppm	145 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Dibutyl tin dilaurate - as Sn	STEL		0.2 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)
	TWA		0.1 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)



Dibutyl tin dilaurate - as Sn	TWA	0.1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEI (02 2014)

Appropriate Engineering Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection Hand Protection:	Additional Information: Use suitable protective gloves if risk of skin contact.
Skin and Body Protection:	Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Avoid contact with eyes. When using do not smoke. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Wash contaminated clothing before reuse. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	liquid
Form:	liquid
Color:	No data available.
Odor:	Mild petroleum/solvent
Odor threshold:	No data available.



pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	137 - 191 °C 279 - 375 °F
Flash Point:	38 °C 100 °F
Evaporation rate:	Slower than Ether
Flammability (solid, gas):	No
Upper/lower limit on flammability or explos	ive limits
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper:	No data available.
Explosive limit - lower:	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.0
Solubility(ies)	
Solubility in water:	Practically Insoluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Heat, sparks, flames.
Incompatible Materials:	Alcohols. Amines. Strong acids. Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes on Inhalation:	of exposure In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes skin irritation.
Eye contact:	Causes serious eye irritation.
Ingestion:	May be harmful if swallowed.



Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Ora Pi	l roduct:	ATEmix: 3,382.19 mg/kg
Der Pi	mal roduct:	ATEmix: 4,782.61 mg/kg
	alation roduct:	ATEmix: 13.76 mg/l ATEmix : 1.5 mg/l
Repeated dose toxicity Product:		No data available.
Skin Corrosion/Irritation Product:		No data available.
Specified substance(s): Methyl n-amyl ketone		in vivo (Rabbit): Moderately irritating , 4 h
	Xylene	in vivo (Rat): Slightly irritating , 24 h
	P-chlorobenzotrifluoride	in vivo (Rabbit): Not irritant (unspecified classification) , 24 - 72 h
	Dibutyl tin dilaurate	In vitro (Human, in vitro reconstituted epidermis model): Not irritant , 15 min
	Diisobutyl ketone	in vivo (Rabbit): Not irritant , 24 - 72 h

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Xylene	Rabbit, 72 h: Moderately irritating
	Rabbit, 1 h: Not irritant



P-0	chlorobenzotrifluoride	Rabbit, 24 h: Not irritant	
Dit	outyl tin dilaurate	Rabbit, 24 h: Highly irritating	
Dii	sobutyl ketone	Rabbit, 24 - 72 h: Not irritant	
Respiratory or Skin Sensitization Product:		n No data available.	
Carcinogenicity Product:		Suspected of causing cancer.	
IARC Mono	graphs on the Evalua	ation of Carcinogenic Risks to Humans:	
	P- chlorobenzotrifluori de	Overall evaluation: Possibly carcinogenic to humans.	
	Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.	
US. National Toxicology Program (NTP) Report on Carcinogens: No carcinogenic components identified			
US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended: No carcinogenic components identified			
Germ Cell I	Mutagenicity		
In vitro Produ	ıct:	No data available.	
In vivo Produ	ıct:	No data available.	
Reproducti Produc		May damage fertility or the unborn child.	
Specific Target Organ Toxicity - Single Exposure Product: No data available.			
Specific Target Organ Toxicity - Repeated ExposureProduct:No data available.			
Target Organs Specific Target Organ Toxicity - Repeated Exposure: hearing			
Aspiration Produc		No data available.	



Other effects:

No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish Product:	No data available.	
Specified substance(s): Methyl n-amyl ketone	LC 50 (Pimephales promelas, 96 h): 131 mg/l	
Xylene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13.41 mg/l Mortality LC 50 (Pimephales promelas, 96 h): 4.7 mg/l	
Ethylbenzene	LC 50 (Oncorhynchus mykiss, 96 h): 4.2 mg/l	
Dibutyl tin dilaurate	LC 50 (Danio rerio, 96 h): 21.2 mg/l	
Aquatic Invertebrates Product:	No data available.	
Specified substance(s): Methyl n-amyl ketone	EC 50 (Daphnia magna, 48 h): > 90.1 mg/l Experimental result, Key study	
Xylene	EC 50 (Daphnia magna, 48 h): 1.8 mg/l Experimental result, Supporting study	
P-chlorobenzotrifluoride	IC 50 (Daphnia magna, 48 h): 2 mg/l Experimental result, Key study	
Ethylbenzene	EC 50 (Daphnia magna, 48 h): 1.8 - 2.4 mg/l Experimental result, Key study	
Dibutyl tin dilaurate	EC 50 (Water flea (Daphnia magna), 24 h): 0.66 mg/l Intoxication EC 50 (Daphnia magna, 48 h): 1.7 - 3.4 mg/l Experimental result, Key study	
Diisobutyl ketone	EC 50 (Daphnia magna, 48 h): 37.2 mg/l Experimental result, Key study	
Chronic hazards to the aquatic environment:		

Chronic hazards to the aquatic environment:

Fish Product:	No data available.
Specified substance(s): Xylene	NOEL (Danio rerio): 0.714 mg/l read-across from supporting substance (structural analogue or surrogate)
Aquatic Invertebrates Product:	No data available.



Toxicity to Aquatic Plants Product:	No data available.	
Persistence and Degradability		
Biodegradation Product:	No data available.	
Specified substance(s): Methyl n-amyl ketone	69 % (28 d) Detected in water. Experimental result, Key study	
P-chlorobenzotrifluoride	19.2 % (28 d) Detected in water. Experimental result, Key study	
Dibutyl tin dilaurate	23 % (39 d) Detected in water. Experimental result, Key study	
Diisobutyl ketone	88 % (20 d) Detected in water. Experimental result, Key study	
BOD/COD Ratio Product:	No data available.	
Bioaccumulative potential Bioconcentration Factor (B0 Product:	CF) No data available.	
Specified substance(s): Xylene		
Хуюнс	Oncorhynchus mykiss, Bioconcentration Factor (BCF): > 5.5 - < 12.2 Aquatic sediment Experimental result, Key study	
P-chlorobenzotrifluoride	Lepomis macrochirus, Bioconcentration Factor (BCF): 121.8 - 202 Aquatic sediment Experimental result, Key study	
Ethylbenzene	Oncorhynchus kisutch, Bioconcentration Factor (BCF): 1 Aquatic sediment Other, Key study	
Partition Coefficient n-octanol / v Product:	water (log Kow) No data available.	
Specified substance(s): Methyl n-amyl ketone	Log Kow: 1.98	
Xylene	Log Kow: 2.77 - 3.15 No Not specified, Not specified	
P-chlorobenzotrifluoride	Log Kow: 3.60 25 °C	
Ethylbenzene	Log Kow: 3.15 Log Kow: 3.13 - 3.14 No Other, Supporting study	
Dibutyl tin dilaurate	Log Kow: 3.12	
Diisobutyl ketone	Log Kow: 2.56	
Mobility in soil:	No data available.	



Other adverse effects:	Harmful to aquatic life with long lasting effects.
13. Disposal considerations	
Disposal methods:	Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Contaminated Packaging:	No data available.

14. Transport information

TDG:

UN1993, FLAMMABLE LIQUID, N.O.S. (Xylene, Butyl Acetate), 3, PG III

CFR / DOT:

UN1993, Flammable liquids, n.o.s. (Xylene, Butyl Acetate), 3, PG III

IMDG:

UN1993, FLAMMABLE LIQUID, N.O.S. (Xylene, Butyl Acetate), 3, PG III

Further Information:

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

15. Regulatory information

US Federal Regulations TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

 Chemical Identity
 Reportable quantity

 P-chlorobenzotrifluoride
 Processor

US. Toxic Substances Control Act (TSCA) Section 5(a)(2) Proposed Significant New Use Rules (SNURs) (40 CFR 721, Subpt E)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
Xylene	100 lbs.
Ethylbenzene	1000 lbs.



Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard Flammable (gases, aerosols, liquids, or solids) Acute toxicity (any route or exposure) Skin Corrosion or Irritation Serious eye damage or eye irritation Carcinogenicity Reproductive toxicity Specific target organ toxicity (single or repeated exposure) Hazards Not Otherwise Classified (HNOC)

US. EPCRA (SARA Title III) Section 304 Extremely Hazardous Substances Reporting Quantities and the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Hazardous Substances

Not Regulated.

US. EPCRA (SARA Title III Section 313 Toxic Chemical Release Inventory (TRI) Reporting

Chemical Identity	<u>% by weight</u>	
Xylene	1.0%	
Ethylbenzene	0.1%	

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

Chemical Identity	Reportable quantity
Xylene	Reportable quantity: 100 lbs.

US State Regulations

US. California Proposition 65



WARNING

Cancer - www.P65Warnings.ca.gov

International regulations

Montreal protocol

Not applicable

Stockholm convention Not applicable

Rotterdam convention Not applicable

Kyoto protocol Not applicable



VOC:

Regulatory VOC (less water and exempt solvent)	:	358 g/l
VOC Method 310	:	34.50 %



Inventory Status: Canada DSL Inventory List:	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Ontario Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Mexico INSQ:	One or more components in this product are not listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
Taiwan Chemical Substance Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	One or more components in this



	product are not listed on or exempt from the Inventory.
EC Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Australia Industrial Chem. Act (AIIC):	One or more components in this product are not listed on or exempt from the Inventory.
Switzerland New Subs Notified/Registered:	One or more components in this product are not listed on or exempt from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date:	05/07/2024
Version #:	3.2
Further Information:	No data available.
Disclaimer:	For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.



Version: 3.2 Revision Date: 05/07/2024

SAFETY DATA SHEET

1. Identification

Product identifier: EUCOTHANE CLEAR PART B Product Code: CUSK G034 000

Recommended use and restriction on use

Recommended use: Coatings Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

EUCLID CHEMICAL COMPANY 19218 REDWOOD ROAD CLEVELAND OH 44110 US

Contact person: Telephone: Emergency telephone number: EH&S Department 216-531-9222 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Physical Hazards	
Flammable liquids	Category 3
Health Hazards	
Acute toxicity (Inhalation - dust and mist)	Category 4
Acute toxicity (Inhalation - vapor)	Category 4
Acute toxicity (Inhalation - dust and mist)	Category 4
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2A
Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 2
Specific Target Organ Toxicity - Single Exposure	Category 3 ^{2.}
Specific Target Organ Toxicity - Repeated Exposure	Category 2 ^{3.}

- 2. Respiratory tract irritation.
- 3. hearing

Unknown toxicity - Health

Acute toxicity, inhalation, vapor 88 %



	Acute toxicity, inhalation, dust or mist	11 %
Environ	nental Hazards	
	Acute hazards to the aquatic environment	Category 3
	Chronic hazards to the aquatic	Category 3

environment

Unknown toxicity - Environment	
Acute hazards to the aquatic environment	78 %
Chronic hazards to the aquatic environment	78 %

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	Flammable liquid and vapor. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. Suspected of causing cancer. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects.
Precautionary Statements	
Prevention:	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Do not breathe dust/fume/gas/mist/vapors/spray. Wash face, hands and any exposed skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/ protective clothing/ eye protection/ face protection. Use personal protective equipment as required. [In case of inadequate ventilation] wear



respiratory protection.

Response:	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see supplemental first aid instructions on this label). IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER or doctor/ physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.
Storage:	Store in a well-ventilated place. Keep container tightly closed. Store locked up.
Disposal:	Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations.
Hazard(s) not otherwise classified (HNOC):	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Homopolymer of HDI	28182-81-2	50 - <100%
Xylene	1330-20-7	10 - <20%
Butyl acetate	123-86-4	10 - <20%
Hexamethylene diisocyanate (HDI)	822-06-0	1 - <5%
Ethylbenzene	100-41-4	1 - <2.5%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Description of necessary first-aid measures

Inhalation:	Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.	
Skin Contact:	Take off immediately all contaminated clothing. Get medical attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.	
Eye contact:	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.	
Ingestion:	Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.	
		2



Personal Protection for First- aid Responders:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.	
Most important symptoms/effe	cts, acute and delayed	
Symptoms:	Respiratory tract irritation. Prolonged or repeated contact with skin may cause redness, itching, irritation and eczema/chapping.	
Hazards:	No data available.	
Indication of immediate medica	I attention and special treatment needed	
Treatment:	Symptoms may be delayed.	
5. Fire-fighting measures		
General Fire Hazards:	Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move containers from fire area if you can do so without risk.	
Suitable (and unsuitable) exting	guishing media	
Suitable extinguishing media:	Use fire-extinguishing media appropriate for surrounding materials.	
Unsuitable extinguishing media:	Avoid water in straight hose stream; will scatter and spread fire.	
Specific hazards arising from the chemical:	Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of vapors or gases to explosive concentrations.	
Special protective equipment and precautions for fire-fighters		
Special fire-fighting procedures:	No data available.	
Special protective equipment for fire-fighters:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.	
6. Accidental release measures		

Personal precautions, protective equipment and emergency procedures:	Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep unauthorized personnel away. Do not touch damaged
	containers or spilled material unless wearing appropriate protective clothing.



Accidental release measures:	In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.
Methods and material for containment and cleaning up:	Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.
Environmental Precautions:	Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water sources or sewer.
7. Handling and storage	
Handling	
Technical measures (e.g. Local and general ventilation):	Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.
Safe handling advice:	Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with eyes. Wash hands thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with skin. Avoid contact with eyes, skin, and clothing.
Contact avoidance measures:	No data available.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Avoid contact with eyes. When using do not smoke. Wash contaminated clothing before reuse. Avoid contact with skin. Contaminated work clothing should not be allowed out of the workplace.
Storage	
Safe storage conditions:	Store locked up. Store in a well-ventilated place. Store in a cool place.
Safe packaging materials:	No data available.
8. Exposure controls/personal protection	

Control Parameters

Occupational Exposure Limits

Chemical Identity	Туре	Exposure Limit Value	es	Source
Xylene	PEL	100 ppm 435 m	ng/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	TWA	20 ppm		US. ACGIH Threshold Limit Values, as amended (01 2022)
Butyl acetate	TWA	50 ppm		US. ACGIH Threshold Limit Values, as amended (03 2016)
	STEL	150 ppm		US. ACGIH Threshold Limit Values, as



				amended (03 2016)
	PEL	150 ppm	710 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Chemical Identity	Туре	Exposure Lim	it Values	Source
Xylene	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	TWA	20 ppm		US. ACGIH Threshold Limit Values, as amended (01 2022)
Butyl acetate	TWA	50 ppm		US. ACGIH Threshold Limit Values, as amended (03 2016)
	STEL	150 ppm		US. ACGIH Threshold Limit Values, as amended (03 2016)
	PEL	150 ppm	710 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Hexamethylene diisocyanate (HDI)	TWA	0.005 ppm		US. ACGIH Threshold Limit Values, as amended (2008)
Ethylbenzene	TWA	20 ppm		US. ACGIH Threshold Limit Values, as amended (2011)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)

Chemical name	Туре	Exposure Limi	t Values	Source
Xylene STEL 150 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)		
	TWA	100 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)
Xylene	STEL	150 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	TWA	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Xylene	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
	STEL	150 ppm	651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Butyl acetate	TWA	50 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
	STEL	150 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Butyl acetate	STEL	150 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)
	TWA	50 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)
Butyl acetate	STEL	150 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (06 2022)
	TWA	50 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological



			Substances (Workers Compensation Board); as amended (06 2022)
Hexamethylene diisocyanate (HDI)	TWA	0.005 ppm	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)
Hexamethylene diisocyanate (HDI)	TWA	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Hexamethylene diisocyanate (HDI)	TWA	0.005 ppm 0.034 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
	CEILING	0.01 ppm	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)

Chemical name	Туре	Exposure Lim	it Values	Source
Xylene	STEL	150 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)
	TWA	100 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)
Xylene	STEL	150 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	TWA	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Xylene	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
	STEL	150 ppm	651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Butyl acetate	TWA	50 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
	STEL	150 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Butyl acetate	STEL	150 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)
	TWA	50 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)
Butyl acetate	STEL	150 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (06 2022)
	TWA	50 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (06 2022)



Hexamethylene diisocyanate (HDI)	TWA	0.005 ppm	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)
Hexamethylene diisocyanate (HDI)	TWA	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Hexamethylene diisocyanate (HDI)	TWA	0.005 ppm 0.034 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
	CEILING	0.01 ppm	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (09 2011)
Ethylbenzene	TWA	20 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Ethylbenzene	TWA	20 ppm	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2013)
Hexamethylene diisocyanate (HDI) (Hexamethylenediamine (with hydrolysis): Sampling time: End of shift.)	15 μg/g (Creatinine in urine)	ACGIH BEI (03 2015)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEI (02 2014)

Appropriate Engineering Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection Hand Protection:	Additional Information: Use suitable protective gloves if risk of skin contact.
Skin and Body Protection:	Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.



Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Avoid contact with eyes. When using do not smoke. Wash contaminated clothing before reuse. Avoid contact with skin. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state:	liquid
Form:	liquid
Color:	No data available.
Odor:	Mild petroleum/solvent
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	137 °C 279 °F
Flash Point:	32.5 °C 90.5 °F
Evaporation rate:	Slower than Ether
Flammability (solid, gas):	No
Upper/lower limit on flammability or explo	osive limits
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper:	No data available.
Explosive limit - lower:	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.100
Solubility(ies)	
Solubility in water:	Practically Insoluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.



10. Stability and reactivity	
Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Heat, sparks, flames.
Incompatible Materials:	Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.
11. Toxicological information	
Information on likely routes of e Inhalation:	exposure In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	Causes skin irritation. May cause an allergic skin reaction.
Eye contact:	Causes serious eye irritation.
Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.
Symptoms related to the physic	cal, chemical and toxicological characteristics
Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.
Information on toxicological eff	rects
Acute toxicity (list all possibl	le routes of exposure)
Oral Product:	ATEmix: 21,059.12 mg/kg
Dermal Product:	ATEmix: 10,000 mg/kg
Inhalation Product:	ATEmix: 11 mg/l ATEmix : 1.5 mg/l



Repeated dose toxicity Product:	No data available.
Skin Corrosion/Irritation Product:	No data available.
Specified substance(s): Homopolymer of HDI	in vivo (Rabbit): Irritating , 24 - 72 h
Xylene	in vivo (Rat): Slightly irritating , 24 h
Butyl acetate	in vivo (Rabbit): Not irritant , 24 - 72 h
Hexamethylene diisocyanate (HDI)	in vivo (Rabbit): Corrosive , 4 - 72 h

Serious Eye Damage/Eye Irritation

d.

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended: No carcinogenic components identified



Germ Cell Mutagenicity

In vitro Product:	No data available.	
In vivo Product:	No data available.	
Reproductive toxicity Product:	No data available.	
Specific Target Organ Toxicity - Single ExposureProduct:No data available.		
Specific Target Organ Toxicity Product:	- Repeated Exposure No data available.	
Specific Target Organ Toxicity - Single Exposure: Respiratory tract irritation. Specific Target Organ Toxicity - Repeated Exposure: hearing		
Aspiration Hazard Product:	No data available.	
Other effects:	No data available.	

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish Product:	No data available.
Specified substance(s): Homopolymer of HDI	LC 50 (Danio rerio, 96 h): 8.9 mg/l
Xylene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13.41 mg/l Mortality LC 50 (Pimephales promelas, 96 h): 4.7 mg/l
Butyl acetate	LC 50 (Pimephales promelas, 96 h): 18 mg/l
Ethylbenzene	LC 50 (Oncorhynchus mykiss, 96 h): 4.2 mg/l
Aquatic Invertebrates Product:	No data available.



Specified substance(s): Xylene	EC 50 (Daphnia magna, 48 h): 1.8 mg/l Experimental result, Supporting study
Butyl acetate	EC 50 (Daphnia sp., 48 h): 44 mg/l Experimental result, Key study
Ethylbenzene	EC 50 (Daphnia magna, 48 h): 1.8 - 2.4 mg/l Experimental result, Key study
Chronic hazards to the aquation	c environment:
Fish Product:	No data available.
Specified substance(s): Xylene	NOEL (Danio rerio): 0.714 mg/l read-across from supporting substance (structural analogue or surrogate)
Aquatic Invertebrates Product:	No data available.
Toxicity to Aquatic Plants Product:	No data available.
Persistence and Degradability	
Biodegradation Product:	No data available.
Specified substance(s): Homopolymer of HDI	1 % (28 d) Detected in water. Experimental result, Key study
Butyl acetate	98 % (28 d) Detected in water. Experimental result, Key study
Hexamethylene diisocyanate (HDI)	42 % (28 d) Detected in water. Experimental result, Key study
BOD/COD Ratio Product:	No data available.
Bioaccumulative potential Bioconcentration Factor (BC Product:	F) No data available.
Specified substance(s): Xylene	Oncorhynchus mykiss, Bioconcentration Factor (BCF): > 5.5 - < 12.2 Aquatic sediment Experimental result, Key study
Hexamethylene diisocyanate (HDI)	Bioconcentration Factor (BCF): 59.6 Aquatic sediment QSAR, Key study



Ethylbenzene	Oncorhynchus kisutch, Bioconcentration Factor (BCF): 1 Aquatic sediment Other, Key study
Partition Coefficient n-octanol / Product:	water (log Kow) No data available.
Specified substance(s): Xylene	Log Kow: 2.77 - 3.15 No Not specified, Not specified
Butyl acetate	Log Kow: 1.78
Hexamethylene diisocyanate (HDI)	Log Kow: 3.20
Ethylbenzene	Log Kow: 3.15 Log Kow: 3.13 - 3.14 No Other, Supporting study
Mobility in soil:	No data available.
Other adverse effects:	Harmful to aquatic life with long lasting effects.
13. Disposal considerations	
Disposal methods:	Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Contaminated Packaging:	No data available.

14. Transport information

TDG:

UN1993, FLAMMABLE LIQUID, N.O.S. (Xylene, Butyl Acetate), 3, PG III

CFR / DOT:

UN1993, Flammable liquids, n.o.s. (Xylene, Butyl Acetate), 3, PG III

IMDG:

UN1993, FLAMMABLE LIQUID, N.O.S. (Xylene, Butyl Acetate), 3, PG III

Further Information:

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D) None present or none present in regulated quantities.



US. Toxic Substances Control Act (TSCA) Section 5(a)(2) Proposed Significant New Use Rules (SNURs) (40 CFR 721, Subpt E)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
Xylene	100 lbs.
Butyl acetate	5000 lbs.
Hexamethylene	100 lbs.
diisocyanate (HDI)	
Ethylbenzene	1000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard Flammable (gases, aerosols, liquids, or solids) Acute toxicity (any route or exposure) Skin Corrosion or Irritation Serious eye damage or eye irritation Respiratory or Skin Sensitization Carcinogenicity Specific target organ toxicity (single or repeated exposure) Hazards Not Otherwise Classified (HNOC)

US. EPCRA (SARA Title III) Section 304 Extremely Hazardous Substances Reporting Quantities and the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Hazardous Substances

Not Regulated.

US. EPCRA (SARA Title III Section 313 Toxic Chemical Release Inventory (TRI) Reporting

Chemical Identity	<u>% by weight</u>
Xylene	1.0%
Hexamethylene	1.0%
diisocyanate (HDI)	
Ethylbenzene	0.1%

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

Chemical Identity	Reportable quantity
Xylene	Reportable quantity: 100 lbs.

US State Regulations

US. California Proposition 65





WARNING Cancer - www.P65Warnings.ca.gov

International regulations

Montreal protocol Not applicable

Stockholm convention Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable

VOC:

Regulatory VOC (less water and exempt solvent)	:	253 g/l
VOC Method 310	:	23.00 %



Inventory Status: Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EC Inventory:	All components in this product are listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	All components in this product are listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	All components in this product are listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	All components in this product are listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	All components in this product are listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Ontario Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Mexico INSQ:	One or more components in this



	product are not listed on or exempt from the Inventory.
Taiwan Chemical Substance Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Australia Industrial Chem. Act (AIIC):	One or more components in this product are not listed on or exempt from the Inventory.
Switzerland New Subs Notified/Registered:	One or more components in this product are not listed on or exempt from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date:	05/07/2024
Version #:	3.2
Further Information:	No data available.
Disclaimer:	For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.