



EUCLID CHEMICAL

# INCRETE COLOR-CRETE CURE WB

## Water-Based Concrete Curing Compound

### Description

**INCRETE COLOR-CRETE CURE WB** is a VOC-compliant, water-based curing compound designed for architectural concrete surfaces. INCRETE COLOR-CRETE CURE WB can be used on both interior and exterior applications and it meets the ASTM C-309 standards for a curing compound. INCRETE COLOR-CRETE CURE WB is offered in clear or colored formulations.

### Primary Applications

Concrete floors, walkways, driveways and integrally-colored concrete.

### Features/Benefits

- Easy to apply
- Ensures moisture retention in newly placed concrete
- Can be factory pre-colored
- Curing architectural surfaces

### Technical Information

<b>Solids content:</b>	Approximately 15%
<b>VOC content:</b>	< 100 g/L
<b>Viscosity:</b>	50 to 400 cps
<b>pH:</b>	8.0 to 9.0
<b>Appearance:</b>	Milky white or colored liquid

### Packaging

INCRETE COLOR-CRETE CURE WB is available in 5 gal (18.9 L) pails. 55 Gal (208.2 L) drums are also available.

### Shelf Life

2 Years in original, unopened containers.

### Coverage

INCRETE COLOR-CRETE CURE WB is applied at a rate of 150 to 200 ft<sup>2</sup>/gal (3.68 to 4.9 m<sup>2</sup>/L). Coverage will vary from the above rates depending on surface texture, application method and texture.

### Specifications/Compliances

- ASTM C 309, Type 1, Class A & B
- AASHTO M 148 Type 1

## Directions for Use

This product is specially formulated for architectural horizontal and vertical concrete surfaces. It can be used over integrally-colored concrete and can be pigmented to match the color. INCRETE COLOR-CRETE CURE WB can be used on driveways, walkways, patios, and pool decks.

Apply INCRETE COLOR-CRETE CURE WB to freshly placed concrete in a thin, even application once the surface water glaze has disappeared. Apply INCRETE COLOR-CRETE CURE WB with a low-pressure pump sprayer or short-napped roller at the recommended application rate.

## Clean-Up

Clean up tools and equipment, overspray and drips with hot, soapy water. Once dry, product is very difficult to remove.

## Precautions/Limitations

- Store between 50 to 90 °F (10 to 32 °C).
- Protect from freezing.
- Do not allow product to puddle on surface.
- Heavy applications, applying in cool or cold weather, or prolonged exposure to moisture may cause this product to have a milky appearance.
- Do not apply if rain or heavy fog is likely within 8 to 12 hours after application.
- Application temperature range is 45 to 95 °F (7 to 35 °C).
- Avoid excessive buildup. Heavy applications will lead to discoloration and poor product performance.
- For professional use only.
- In all cases, consult the SDS before use.

Rev. 08.19

**WARRANTY:** The Euclid Chemical Company ("Euclid") solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Euclid, no other representations or statements made by Euclid or its representatives, in writing or orally, shall alter this warranty. EUCLID MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Euclid product fails to conform with this warranty, Euclid will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Euclid does not authorize anyone on its behalf to make any written or oral statements which in any way alter Euclid's installation information or instructions in its product literature or on its packaging labels. Any installation of Euclid products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Euclid's products for the Buyer's intended purposes.