



INCRETE COLOR RELEASE

COLORED STAMP-TOOL RELEASING POWDER

PACKAGING

20 lb (9.1 kg) pails

YIELD

Approximately 800 to 1000 ft² / 20 lb
(74 to 93 m² / 9.07 kg) pail.

APPEARANCE

Dry powder that comes in clear (looks white dry) and 35 standard colors.

CLEAN UP

Clean tools and equipment with water.

SHELF LIFE

4 years in original, unopened container.

SPECIFICATIONS AND COMPLIANCES

ASTM C 979

BRIEF OVERVIEW

INCRETE COLOR RELEASE contains a specially-formulated releasing agent that forms a moisture barrier between the stamping tools and wet concrete, allowing easy release of imprinting tools. It is a dry-shake material applied directly on top of the concrete, INCRETE COLOR HARDENER, or INCRETE COLOR-CRETE prior to stamping. The colored releasing agent contains iron-oxide pigments that add color and depth to the stamped surface.

PRODUCT CHARACTERISTICS

ADVANTAGES

- Provides a barrier that prevents suction when removing stamps from textured concrete.
- Reduces the need for touch-ups.
- Rich-looking antique effect.
- Creates a two-toned, highlighted appearance.
- Deeper textures and grout lines when applied over color hardeners.

COMMON USES

- Stamp-tool release
- Secondary-color accent on plain or colored concrete
- Texturing
- Embossing
- Stamped overlays

COMMON METHODS

- Broadcast by hand or dash brush

PHYSICAL PROPERTIES

- Dry-shake material applied directly on top of wet concrete

DIRECTIONS FOR USE

PREPARATION

All surrounding areas should be protected from dust contamination. Poly sheeting is recommended for masking.

APPLICATION

After all color hardener is applied and/or final troweling is completed, and when bleed water has evaporated from the surface, INCRETE COLOR RELEASE should be applied.

BROADCAST PROCEDURE

Empty half of the contents of one pail into a clean, dry container and aerate material to loosen any compaction before broadcasting onto a surface. Apply lightly and evenly over area using a casting motion, using caution in windy conditions. Two applications may be required for uniform coverage. For optimal result, a dash brush may be used to broadcast INCRETE COLOR RELEASE. Euclid Chemical recommends that you apply one or two rows ahead of the stamping tools rather than covering the entire surface at once.

DIRECTIONS FOR USE CONT.

FINISHING

After stamping and after the concrete has set and dried, remove the excess color by rinsing with potable water. While the concrete surface is wet, spray on a solution of 1 part muriatic acid and 10 parts water, and use a straw broom or lightweight, acid-resistant brush to agitate the surface. This will remove excess INCRETE COLOR RELEASE from the high points in the stamp pattern while retaining the secondary color in the deeper areas and grout lines. Take care not to wash secondary color off completely. Use a lighter, quicker rinsing action for the grout lines and deeper indentations. Removing most of the release from the high spots, and leaving more of the color in the deeper areas will enhance antique effect for a beautiful, more natural finish.

After the concrete has been washed and dried thoroughly, apply any of the Euclid Chemical or Increte branded acrylic clear sealers to enhance the color and to protect the surface. Refer to appropriate technical data sheets for application methods and coverage rates.

PRECAUTIONS/LIMITATIONS

- For use on stamped concrete products only.
- Be sure to mask off areas not being treated with color.
- For professional use only.
- In all cases, consult the Safety Data Sheet before use.

Rev. 07.21

WARRANTY: The Euclid Chemical Company ("Euclid") solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Euclid, no other representations or statements made by Euclid or its representatives, in writing or orally, shall alter this warranty. EUCLID MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Euclid product fails to conform with this warranty, Euclid will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Euclid does not authorize anyone on its behalf to make any written or oral statements which in any way alter Euclid's installation information or instructions in its product literature or on its packaging labels. Any installation of Euclid products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Euclid's products for the Buyer's intended purposes.