



EUCLID CHEMICAL

INCRETE LIQUID COLOR DISPERSION

GROUT COLORANT

PACKAGING

1 qt (0.94 L) container

YIELD

Each color requires a different amount of pigment per bag of grout. See page 2 for the complete list or check with Euclid Chemical's technical department.

APPEARANCE

35 standard colors - custom color matching available.

CLEAN UP

Clean tools and equipment, and spills with hot, soapy water.

SHELF LIFE

2 years in original, unopened container

SPECIFICATIONS AND COMPLIANCES

VOC Content: <600 g/L

BRIEF OVERVIEW

Specially blended liquid pigments, specifically designed for use with the INCRETE TEXTURE-CRETE overlay system. Highly concentrated, INCRETE LIQUID COLOR DISPERSION can be used to add color to any cementitious product. These colorants come in 35 standard colors with custom color matching available. UV and weather stable, INCRETE LIQUID COLOR DISPERSION can be used outdoors as well as indoors.

PRODUCT CHARACTERISTICS

ADVANTAGES

- Easy to mix
- Will not fade
- Dust-free
- Consistent color
- May be also used with the INCRETE LEVEL TOP STAIN overlay systems

PHYSICAL PROPERTIES

- Water-based, liquid color concentrates

COMMON USES

- INCRETE TEXTURE-CRETE
- INCRETE SPRAY-DECK GROUT
- INCRETE SINGLE COMPONENT SPRAY-DECK GROUT

COMMON METHODS

- Trowelable (horizontal applications)
- Pumpable
- Form and pour

TECHNICAL INFORMATION

Weight per gallon: 9.6-17.1 lbs

Pigment Solids: 33-68%

VOC Content: 101-531 g/L

DIRECTIONS FOR USE

Shake INCRETE LIQUID COLOR DISPERSION well before use. With a syringe, measure the correct amount of colorant based on the color chart information. Add the colorant to the mixing water and blend lightly before adding to the grout. Use a 50 lb (22.7 kg) bag of white grout as the base and mix according to the specific product instructions. For best results, blend enough colored water for the entire project if possible.

PRECAUTIONS/LIMITATIONS

- Protect from freezing.
 - For professional use only.
 - In all cases, consult the Safety Data Sheet before use.
-

STANDARD COLORS & DOSE

COLOR	ADDITION PER 50 LB (22.7 KG) BAG
Adobe Buff	0.08 fl oz (2.5 ml)
Antique White	2 fl oz (59 ml)
Austin Buff	1.50 fl oz (45 ml)
Autumn Brown	3.3 fl oz (97.6 ml)
Black	6 fl oz (177.6 ml)
Brick Red	4.8 fl oz (142 ml)
Buckskin	1.75 fl oz (52 ml)
Charcoal	1.48 fl oz (44 ml)
Coral	0.12 fl oz (3.5 ml)
Desert Tan	4.5 fl oz (133.2 ml)
Fiesta	0.63 fl oz (19 ml)
Gray	0.60 fl oz (18 ml)
Harvest Sand	0.08 fl oz (2.5 ml)
Kool White	0.15 fl oz (4.5 ml)
Maplewood	3.8 fl oz (112 ml)
Peach	0.24 fl oz (7 ml)
Pewter	0.10 fl oz (3 ml)
Philly Blue	1.25 fl oz (37 ml)
Redwood	8 fl oz (236 ml)
Rust Brown	7 fl oz (207 ml)
Sabal	7 fl oz (207 ml)
Safety Yellow	3.75 fl oz (111 ml)
Saltillo	2 fl oz (60 ml)
Sand Buff	2.25 fl oz (67 ml)
Sandstone	0.7 fl oz (21 ml)
Seafoam Green	1.5 fl oz (44.4 ml)
Silver Gray	0.2 fl oz (6 ml)
Sky Blue	11 fl oz (325.6 ml)
Slate	2.2 fl oz (65 ml)
Sun Buff	0.60 fl oz (17.5 ml)
Sun Gray	0.30 fl oz (9 ml)
Teal	0.27 fl oz (8 ml)
Terra Cotta	8.4 fl oz (248 ml)
Tile Red	8 fl oz (236 ml)
Walnut	8 fl oz (236 ml)
White	7 fl oz (207 ml)

Rev. 07.21

WARRANTY: The Euclid Chemical Company ("Euclid") solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Euclid, no other representations or statements made by Euclid or its representatives, in writing or orally, shall alter this warranty. EUCLID MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Euclid product fails to conform with this warranty, Euclid will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Euclid does not authorize anyone on its behalf to make any written or oral statements which in any way alter Euclid's installation information or instructions in its product literature or on its packaging labels. Any installation of Euclid products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Euclid's products for the Buyer's intended purposes.