



INCRETE SOLV-KLEEN

CLEAN-UP AND FLOOR STRIPPER PRODUCT

PACKAGING

1 gal (3.8 L) and 5 gal (18.9 L) units.
55 Gal drums available upon request.

APPEARANCE

Clear, low-viscosity liquid

CLEAN UP

Avoid spilling or splashing. Spills will evaporate

SHELF LIFE

3 years in original, unopened container

SPECIFICATIONS AND COMPLIANCES

VOC Content: 862 g/L

BRIEF OVERVIEW

INCRETE SOLV-KLEEN is a blended-solvent product used to clean up spills, application tools, and equipment.

PRODUCT CHARACTERISTICS

ADVANTAGES

- High strength for fast clean-up
- Blend of solvents results in long open time
- Leaves no residue

COMMON APPLICATION METHODS

- Spray
- Pour
- Brush
- Rags

COMMON USES

- Clean up tools and equipment
- Removal of resin-based curing membranes and sealers

DIRECTIONS FOR USE

MIXING

INCRETE SOLV-KLEEN requires no premixing. The product is ready for use directly from the container.

CLEANING SPRAYERS

Run INCRETE SOLV-KLEEN through equipment until coating residue is completely flushed out. Capture runoff and excess in an approved container and dispose of in accordance with local regulations.

SEALER STRIPPING

Apply INCRETE SOLV-KLEEN directly to the area to be stripped. Keep the area wet and allow to soften for 5 to 10 minutes. Reapply additional solvent and begin resin removal by scraping or scrubbing. Additional applications may be necessary to remove all the sealer.

PRECAUTIONS/LIMITATIONS

- **FLAMMABLE!** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Close ventilation air intakes if they will distribute solvent odor into adjoining occupied sections of buildings.
- Wear appropriate hand/skin/eye/face/respiratory protections.
- For professional use only.
- In all cases, consult the Safety Data Sheet before use.

WARRANTY: The Euclid Chemical Company ("Euclid") solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Euclid, no other representations or statements made by Euclid or its representatives, in writing or orally, shall alter this warranty. EUCLID MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Euclid product fails to conform with this warranty, Euclid will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Euclid does not authorize anyone on its behalf to make any written or oral statements which in any way alter Euclid's installation information or instructions in its product literature or on its packaging labels. Any installation of Euclid products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Euclid's products for the Buyer's intended purposes.