



INCRETE UNI-STRIPP

UNIVERSAL STRIPPER FOR ALL PAINTS AND COATINGS

PACKAGING

1 gal (3.8 L) and 5 gal (18.9 L) units

YIELD

50 ft²/gal @ 1/32 in (1.22 m²/L @ 0.8 mm)

APPEARANCE

Opaque gel

CLEAN UP

Clean tools and equipment with INCRETE SOLV-KLEEN before material dries. Control waste runoff.

SHELF LIFE

3 years in original, unopened container

SPECIFICATIONS AND COMPLIANCES

Viscosity: 60 KU @ 70 °F (21 °C)

BRIEF OVERVIEW

INCRETE UNI-STRIPP universal stripper is designed to remove a wide variety of paints, stains, and varnishes which are oil or water-based, including latex alkyds, stains, enamels, lacquers and clear paints. Unlike other paint removers, INCRETE UNI-STRIPP can remove difficult coatings such as two-component epoxy or urethane sealers from concrete surfaces. INCRETE UNI-STRIPP is also very effective on mastic adhesives and glues.

PRODUCT CHARACTERISTICS

ADVANTAGES

- Citrus scented
- Can remove multiple layers
- Can be cleaned with water
- Thick enough to use on vertical surfaces

COMMON USES

- Interior/Exterior
- Horizontal, vertical, overhead
- Remove sealers, paints & coatings
- Removes most glues and mastics

COMMON METHODS

- Brush
- Roller
- Trowel
- Squeegee

DIRECTIONS FOR USE

INCRETE UNI-STRIPP is ready to use. A small test patch should be applied to the coated surface to determine the dwell time needed to soften and remove the coating. Shake or mix prior to use. Application can be by brush, roller or trowel. INCRETE UNI-STRIPP may be worked in with a stiff bristled broom for added effectiveness. Normally two-component epoxy systems need an extended dwell time. Thermoplastic acrylics often require less than 30-minute dwell times. For best results cover all applications with plastic sheeting and remove any trapped air. Loosened coatings can then be scraped or rinsed with a power washer. Control waste/runoff in accordance with local environmental guidelines.

PRECAUTIONS/LIMITATIONS

- Use with adequate ventilation.
- For professional use only.
- In all cases, consult the Safety Data Sheet before use.

WARRANTY: The Euclid Chemical Company ("Euclid") solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Euclid, no other representations or statements made by Euclid or its representatives, in writing or orally, shall alter this warranty. EUCLID MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Euclid product fails to conform with this warranty, Euclid will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Euclid does not authorize anyone on its behalf to make any written or oral statements which in any way alter Euclid's installation information or instructions in its product literature or on its packaging labels. Any installation of Euclid products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Euclid's products for the Buyer's intended purposes.