EUCO-FILL 50

ANTI-WASHOUT ADMIXTURE



DESCRIPTION

EUCO-FILL 50 is a liquid admixture designed to minimize the loss of cement and fine aggregates during the placement of backfill under water or when water is flowing through the placement area. It can also be used with cement-based grouts where water is a problem.

PRIMARY APPLICATIONS

- · Rockfill mixes
- · Paste backfill mixes
- Grouting

FEATURES/BENEFITS

· Minimizes washout of cement and fine aggregates

TECHNICAL DATA

EUCO-FILL 50 can also be used at low dosages to reduce segregation in a mix.

PACKAGING

EUCO-FILL 50 is available in bulk, 275 gal (1041L) totes and 55 gal (208L) drums.

SHELF LIFE

6 months in original, unopened container.

DOSAGE

EUCO-FILL 50 is typically used at dosage rates of 5 to 29 oz/ton (325 to 2100 ml/tonne) of backfill for most applications. At higher dosage rates, set retardation is likely to occur.

DIRECTIONS FOR USE

EUCO-FILL 50 is added to the mix after any other admixtures. If the consistency or slump of the mix is adjusted with water, it must be done before the addition of EUCO-FILL 50.

PRECAUTIONS/LIMITATIONS

- Do not allow EUCO-FILL 50 to freeze.
- Do not add water to the mix after the addition of EUCO-FILL 50.
- Significant set retardation may occur with the use of this product.
- In all cases, consult the Safety Data Sheet before use.

