

Revision Date: 07/29/2015

SAFETY DATA SHEET

1. Identification

Material name: NS METALLIC GROUT 50 LB BAG MTO

Material: 081 50

Recommended use and restriction on use

Recommended use: Cement, Portland, chemicals

Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Euclid Admixture Canada Inc.

2835 Grand-Allee

Saint Hubert QC J4T 2R4

CA

Contact person: EH&S Department **Telephone:** (450)465-2233

Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Acute toxicity (Inhalation - dust and Category 4

mist)

Skin Corrosion/Irritation Category 2
Serious Eye Damage/Eye Irritation Category 1
Skin sensitizer Category 1B
Carcinogenicity Category 1A
Specific Target Organ Toxicity - Category 3

Single Exposure

Unknown toxicity - Health

Acute toxicity, oral 67.84 %
Acute toxicity, dermal 94.31 %
Acute toxicity, inhalation, vapor 100 %
Acute toxicity, inhalation, dust or mist 96.84 %

Unknown toxicity - Environment

Acute hazards to the aquatic 98.18 %

environment

Chronic hazards to the aquatic 100 %

environment

Label Elements

Hazard Symbol:



Revision Date: 07/29/2015



Signal Word: Danger

Hazard Statement: Harmful if inhaled.

Causes skin irritation.

Causes serious eye damage. May cause an allergic skin reaction.

May cause cancer.

May cause respiratory irritation.

Precautionary Statement: Prevention:

Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a

well-ventilated area. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Contaminated work

clothing must not be allowed out of the workplace. Obtain special

instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.

Response: IF INHALED: Remove person to fresh air and keep comfortable for

breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Immediately call a POISON CENTER/doctor. Specific treatment (see this label). Wash contaminated clothing before reuse.

Storage: Store locked up. Store in well-ventilated place. Keep container tightly

closed.

Disposal: Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Other hazards which do not result in GHS classification:

None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	30 - 60%
Portland cement	65997-15-1	30 - 60%
Iron oxide	1309-37-1	15 - 40%
**	**	3 - 7%
Fumed silica	69012-64-2	1 - 5%
Calcium salt	7778-18-9	1 - 5%



Revision Date: 07/29/2015

Carbon	7440-44-0	0.5 - 1.5%
Silicon	7440-21-3	0.1 - 1%

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Trade secret information: ** A specific chemical identity and/or percentage of composition has been

withheld as a trade secret.

4. First-aid measures

Ingestion: Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.

Inhalation: Move to fresh air.

Skin Contact: Immediately flush with plenty of water for at least 15 minutes while

removing contaminated clothing and shoes. Wash contaminated clothing

before reuse. Get medical attention.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. If easy to do,

remove contact lenses. Call a physician or poison control center

immediately.

Most important symptoms/effects, acute and delayed

Symptoms: Prolonged or repeated contact with skin may cause redness, itching,

irritation and eczema/chapping. Extreme irritation of eyes and mucous membranes, including burning and tearing. Respiratory tract irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical:

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Self-contained breathing apparatus and full protective clothing must be

worn in case of fire.



Revision Date: 07/29/2015

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:

See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate

protective clothing. Keep unauthorized personnel away.

Methods and material for containment and cleaning Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

up:

Notification Procedures:

In the event of a spill or accidental release, notify relevant authorities in

accordance with all applicable regulations.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or

spillage if safe to do so.

7. Handling and storage

Precautions for safe handling:

Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not get in eyes. Wash hands thoroughly after handling. Avoid contact with skin. Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust.

Conditions for safe storage, including any incompatibilities:

Store locked up.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Crystalline Silica	TWA	0.025	US. ACGIH Threshold Limit Values
(Quartz)/ Silica Sand -		mg/m3	(2011)
Respirable fraction.			
Crystalline Silica	TWA	2.4	US. OSHA Table Z-3 (29 CFR
(Quartz)/ Silica Sand -		millions of	1910.1000) (2000)
Respirable.		particles	
		per cubic	
		foot of air	
	TWA	0.1 mg/m3	US. OSHA Table Z-3 (29 CFR
			1910.1000) (2000)
Crystalline Silica	TWA	0.3 mg/m3	US. OSHA Table Z-3 (29 CFR
(Quartz)/ Silica Sand -		_	1910.1000) (2000)
Total dust.			, , ,
Portland cement -	TWA	1 mg/m3	US. ACGIH Threshold Limit Values
Respirable fraction.			(2011)
Portland cement - Total	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air
dust.			Contaminants (29 CFR 1910.1000)
			(02 2006)





Revision Date: 07/29/2015

Portland cement -	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air
Respirable fraction.	PEL	5 1119/1113	Contaminants (29 CFR 1910.1000)
Respirable fraction.			(02 2006)
Portland cement	TWA	50 millions	US. OSHA Table Z-3 (29 CFR
Fortiand Cement	1 447	of particles	1910.1000) (2000)
		per cubic	1910.1000) (2000)
		foot of air	
Iron oxide - Respirable	TWA	5 mg/m3	US. ACGIH Threshold Limit Values
fraction.	1 7 7 7	3 mg/m3	(2011)
Iron oxide - Fume.	PEL	10 mg/m3	US. OSHA Table Z-1 Limits for Air
Tion oxide Tame.	1	To mg/ms	Contaminants (29 CFR 1910.1000)
			(02 2006)
Fumed silica	TWA	20 millions	US. OSHA Table Z-3 (29 CFR
		of particles	1910.1000) (2000)
		per cubic	(====)
		foot of air	
	TWA	0.8 mg/m3	US. OSHA Table Z-3 (29 CFR
	1 4 4 7	3	1910.1000) (2000)
Calcium salt - Inhalable	TWA	10 mg/m3	US. ACGIH Threshold Limit Values
fraction.			(2011)
Calcium salt - Total	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air
dust.		S .	Contaminants (29 CFR 1910.1000)
			(02 2006)
Calcium salt -	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air
Respirable fraction.		Ü	Contaminants (29 CFR 1910.1000)
•			(02 2006)
Carbon - Respirable	TWA	2 mg/m3	US. ACGIH Threshold Limit Values
fraction.			(2011)
Carbon - Respirable	TWA	3 mg/m3	US. ACGIH Threshold Limit Values
particles.			(03 2014)
Carbon - Inhalable	TWA	10 mg/m3	US. ACGIH Threshold Limit Values
particles.			(03 2014)
Carbon - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air
			Contaminants (29 CFR 1910.1000)
			(02 2006)
Carbon - Respirable	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air
fraction.			Contaminants (29 CFR 1910.1000)
			(02 2006)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air
			Contaminants (29 CFR 1910.1000)
Carbon Total diret	DEI	45	(02 2006)
Carbon - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air
			Contaminants (29 CFR 1910.1000)
Carban	T\\\/\^	AE maillione	(02 2006)
Carbon	TWA	15 millions	US. OSHA Table Z-3 (29 CFR
		of particles per cubic	1910.1000) (2000)
		foot of air	
Carbon - Total dust.	TWA	50 millions	US. OSHA Table Z-3 (29 CFR
Garbon - Fotal dust.	1 * * ^ _	of particles	1910.1000) (2000)
		per cubic	1010.1000) (2000)
		foot of air	
Carbon - Respirable	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR
fraction.	1 4 4 / 3	3 mg/m3	1910.1000) (2000)
Carbon - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR
Carbon Total dust.	1 4 4 7	15 mg/ms	33. 33111 Table 2 3 (23 Of IX



Revision Date: 07/29/2015

			1910.1000) (2000)
Carbon - Respirable	TWA	15 millions	US. OSHA Table Z-3 (29 CFR
fraction.		of particles	1910.1000) (2000)
		per cubic	
		foot of air	
Silicon - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air
			Contaminants (29 CFR 1910.1000)
			(02 2006)
Silicon - Respirable	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air
fraction.			Contaminants (29 CFR 1910.1000)
			(02 2006)





Revision Date: 07/29/2015

Chemical name	type	Exposure Limit Values	Source
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Crystalline Silica (Quartz)/ Silica Sand - Respirable.	TWAEV	0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Portland cement - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Portland cement - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Portland cement	TWAEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Portland cement - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Portland cement - Respirable dust.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Iron oxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Iron oxide - Dust as Fe	TWA	5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Iron oxide - Fume as Fe	STEL	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Iron oxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97,



Revision Date: 07/29/2015

			as amended) (07 2007)
Iron oxide - Fume as Fe	TWA	5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Iron oxide - Respirable fraction.	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Iron oxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Iron oxide - Dust and fume as Fe	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Fumed silica - Total fume.	TWA	4 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Fumed silica - Respirable fume.	TWA	1.5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Fumed silica - Respirable.	TWAEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Fumed silica - Respirable dust and/or fume.	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium salt - Inhalable	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium salt - Inhalable fraction.	TWAEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium salt - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium salt - Respirable dust.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.



Revision Date: 07/29/2015

Individual protection measures, such as personal protective equipment

General information: Provide easy access to water supply and eye wash facilities. Good general

ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable

level.

Eye/face protection: Wear a full-face respirator, if needed. Wear safety glasses with side shields

(or goggles) and a face shield.

Skin Protection

Hand Protection: Use suitable protective gloves if risk of skin contact.

Other: Wear suitable protective clothing. Wear chemical-resistant gloves,

footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific

information.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from

local supervisor.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and

immediately after handling the product. Do not get in eyes. Wash contaminated clothing before reuse. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state: solid
Form: Powder
Color: Gray
Odor: Odorless

Odor threshold:

pH:

No data available.

Flash Point:

No data available.

No data available.

No data available.

Flammability (solid, gas): No Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

Explosive limit - upper (%):

Explosive limit - lower (%):

Vapor pressure:

Vapor density:

No data available.

No data available.

No data available.

No data available.



Revision Date: 07/29/2015

Relative density: 3.45

Solubility(ies)

Solubility in water:
Solubility (other):
No data available.
Partition coefficient (n-octanol/water):
No data available.
No data available.
Decomposition temperature:
No data available.
Viscosity:
No data available.

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability: Material is stable under normal conditions.

Possibility of Hazardous

Reactions:

No data available.

Conditions to Avoid: Avoid heat or contamination.

Incompatible Materials: No data available.

Hazardous Decomposition

Products:

Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Ingestion: May be ingested by accident. Ingestion may cause irritation and malaise.

Inhalation: In high concentrations, vapors, fumes or mists may irritate nose, throat and

mucus membranes.

Skin Contact: May be harmful in contact with skin. Causes skin irritation.

Eye contact: Causes serious eye damage.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: ATEmix: 20,530.61 mg/kg

Dermal

Product: ATEmix: 3,633 mg/kg

Inhalation

Product: ATEmix: 1.92 mg/l



Revision Date: 07/29/2015

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Iron oxide in vivo (Rabbit, 1 - 72 hrs): Not irritating

Calcium salt in vivo (Rabbit, 72 hrs): Not irritating

Carbon Irritating

Silicon in vivo (Rabbit, 1 hrs): Not irritating

Respiratory or Skin Sensitization

Product: No data available.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Crystalline Silica

(Quartz)/ Silica

Sand

US. National Toxicology Program (NTP) Report on Carcinogens:

Crystalline Silica Known To Be Human Carcinogen.

Overall evaluation: Carcinogenic to humans.

(Quartz)/ Silica

Sand

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.



Revision Date: 07/29/2015

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Calcium salt LC 50 (Fathead minnow (Pimephales promelas), 96 h): > 1,970 mg/l

Mortality

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Calcium salt LC 50 (Water flea (Daphnia magna), 24 h): > 1,970 mg/l Mortality

LC 50 (Water flea (Ceriodaphnia dubia), 24 h): > 1,940 mg/l Mortality LC 50 (Water flea (Ceriodaphnia dubia), 48 h): > 1,970 mg/l Mortality LC 50 (Water flea (Ceriodaphnia dubia), 48 h): > 1,910 mg/l Mortality

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Iron oxide LOAEL (Pimephales promelas, 33 d): 1.6 mg/l experimental result

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation



Revision Date: 07/29/2015

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative Potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)
Product:
No data available.

Mobility in Soil: No data available.

Other Adverse Effects: No data available.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.



Revision Date: 07/29/2015

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u> <u>Reportable quantity</u>

Chromium 5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

Chemical Identity Reportable quantity

Chromium 5000 lbs.

SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Crystalline Silica (Quartz)/	500 lbs
Silica Sand	
Portland cement	500 lbs
Iron oxide	500 lbs
Fused calcium aluminate	500 lbs
Fumed silica	500 lbs
Calcium salt	500 lbs
Carbon	500 lbs
Silicon	500 lbs

SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Crystalline Silica (Quartz)/ Silica Sand Portland cement Iron oxide Fumed silica Calcium salt



Revision Date: 07/29/2015

US. Massachusetts RTK - Substance List

Chemical Identity

Crystalline Silica (Quartz)/ Silica Sand Portland cement

Iron oxide
Fumed silica
Calcium salt

Chromium

Chemical Identity

Crystalline Silica (Quartz)/ Silica Sand Portland cement Iron oxide Fumed silica Calcium salt

US. Pennsylvania RTK - Hazardous Substances

US. Rhode Island RTK

No ingredient regulated by RI Right-to-Know Law present.

Other Regulations:

Regulatory VOC (less water 0 g/l

and exempt solvent):

VOC Method 310: 0.00 %

Inventory Status:

Australia AICS: All components in this product are listed on or

exempt from the Inventory.

Canada DSL Inventory List: All components in this product are listed on or

exempt from the Inventory.

EINECS, ELINCS or NLP: One or more components in this product are

not listed on or exempt from the Inventory.

Japan (ENCS) List: One or more components in this product are

not listed on or exempt from the Inventory.

China Inv. Existing Chemical Substances:

All components in this product are listed on or

exempt from the Inventory.

Korea Existing Chemicals Inv. (KECI): All components in this product are listed on or

exempt from the Inventory.

Canada NDSL Inventory: One or more components in this product are

not listed on or exempt from the Inventory.

Philippines PICCS: One or more components in this product are

not listed on or exempt from the Inventory.



Revision Date: 07/29/2015

US TSCA Inventory:

All components in this product are listed on or

exempt from the Inventory.

New Zealand Inventory of Chemicals:

All components in this product are listed on or

exempt from the Inventory.

Japan ISHL Listing:

One or more components in this product are

not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are

not listed on or exempt from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date: 07/29/2015

Version #: 1.0

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard

information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including

the safe use of the product under every foreseeable condition.