



EUCON™ PAVERTITE

EFFLORESCENCE CONTROLLING ADMIXTURE FOR CONCRETE MASONRY

EUCLID CHEMICAL

PRODUCT INFORMATION

PACKAGING

Available in bulk, 275 gal (1041 L) totes, 55 gal (208 L) drums and 5 gal (18.9 L) pails

SHELF LIFE

6 months in original, unopened container

TECHNICAL INFORMATION

Appearance: White Liquid
Specific Gravity ~ 1.02
Freeze Point ~ 20°F (-6.7°C)

DESCRIPTION

EUCON PAVERTITE is a concentrated, high performance admixture developed specifically for the paver / hardscape and roof tile industries. Mixes treated with EUCON PAVERTITE exhibit better material flow, compaction, and texture uniformity. Throughout its dosage range, EUCON PAVERTITE adds strength, resists moisture, and reduces the potential for secondary efflorescence.

PRODUCT CHARACTERISTICS

FEATURES & BENEFITS

- Reduced absorption to meet performance criteria
- Efflorescence control improves color/retention
- Higher density for maximized service life

PRIMARY APPLICATIONS

- Concrete pavers, slabs
- Segmental retaining wall units
- Concrete roofing tile

PRECAUTIONS/LIMITATIONS

- EUCON PAVERTITE performs optimally with quality materials and proper mix designs/mix consistency - consult your Euclid Chemical representative for assistance with recommended mix designs and dosage rates.
- DO NOT allow EUCON PAVERTITE to freeze. Once the product has frozen, it becomes unusable.
- EUCON PAVERTITE, when stored in bulk, may need occasional re-circulation; use mechanical agitation if necessary, but never agitate with air. Contact your local Euclid Chemical sales representative for assistance with this process.
- In all cases, consult the Safety Data Sheet before use.

DIRECTIONS FOR USE

EUCON PAVERTITE is intended for use at a rate of 6 - 12 oz/100 lbs (391 - 782 mL/100 kg) of cementitious materials. EUCON PAVERTITE is compatible with other EUCON plasticizing, efflorescence controlling, and accelerating admixtures. Add EUCON PAVERTITE to the mixture after all of the water has been added and mix adequately (as needed based on mixer type). Any admixture products used in combination should be added separately, and in accordance with directions for their use.

WARRANTY: The Euclid Chemical Company ("Euclid") solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Euclid, no other representations or statements made by Euclid or its representatives, in writing or orally, shall alter this warranty. EUCLID MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Euclid product fails to conform with this warranty, Euclid will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Euclid does not authorize anyone on its behalf to make any written or oral statements which in any way alter Euclid's installation information or instructions in its product literature or on its packaging labels. Any installation of Euclid products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Euclid's products for the Buyer's intended purposes.